



Underground scooptram WJ-0.6

Model:WJ-0.6
 Bucket Volume:0.6m³
 Rated Load Capacity:1200kg
 Size:4850mm*1100mm*1760mm
 Weight :4200kg



Product Feature

- Flexible , Wide application range
- Simplify the tunnel structure
- Adopt articulated structure, reduces failure rate;
- Shovel strength



Main Component

- Engine
Model:YANMAR 4TNV98T
- Hydraulic motor
Model:Rexroth A2FM90
- Hydraulic pump
Model:Rexroth A4VG
- Double pump
PERMCO P124
- Drive axle
Model: Chinese Brand



Product Advantage

- Economical and energy-saving
- Safe and reliable
- Low maintenance cost



Matching system

- The following systems can be customized according to customer requirements
- Self-lubrication system
 - Fire extinguishing system



Technical Specification

Main Technical Specification		CANW WJ-0.6
Standard bucket volume	标准斗容	0.6m³
Rated Load Capacity	额定载重	1200 kg
Relieving Force	铲取力	38KN
Pulling Force	牵引力	45KN
Climbing Capacity	爬坡能力	Max14°
Net weight	净车重量	4200 kg
Engine	发动机	
Internal combustion engine	内燃机	YANMAR 4TNV98T
Rated power	额定功率	56.5kw/2200r/min
Emission standard	排放标准	Tier III. Stagelll
Hydraulic system	液压系统	
Hydraulic motor	液压马达	Rexroth A2FM90
Oil hydraulic pump	液压泵	Rexroth A4VG
Double pump	双联泵	PERMCO P124
Rive axle	桥	Chinese
Braking system	制动系统	posi-stop
Tyre		轮胎
Type	型号	7.50R15
Rack		机架
Rack	机架	High-tensile structural steel
Diesel fuel tank	柴油机燃油箱	130 L
Hydraulic oil tank	液压油箱	110 L
Articulated	铰链	Adjustable
Cab		驾驶室
Type	类型	ROPS/FOPS
Size		尺寸
Length	长	4850±100 mm
Width	宽	1100±50 mm
High	高	1760±50 mm
Ground Clearance	离地间隙	220mm
Steering Radius		转弯半径
Turning angle	转弯角度	±38°
Inside Steering Radius	内转弯半径	≤2400 mm
Outside Steering Radius	外转弯半径	≤4000 mm