



## Underground transport vehicles RU-6

Model:RU-6  
Rated passenger:6  
Rated Load Capacity:1000kg  
Size:4750mm\*2040mm\*2230mm  
Weight :6000kg



### Product Feature

- Flexible , Wide application range
- Simplify the tunnel structure
- The braking system is Posi-stop,Closed cab, safe and comfortable
- Integral skeleton carriage with high strength;



### Main Component

- Engine  
Model:Chinese Brand
- Hydraulic torque convertor  
Model:DANA C270
- Gearbox  
Model:DANA 12060A
- Drive axle  
Model: DANA 211/111



### Product Advantage

- Economical and energy-saving
- Safe and reliable
- Low maintenance cost



### Speed

- 0-6.0 km/h
- 0-13.0 km/h
- 0-23.0 km/h



## Technical Specification

Main Technical Specification		CANW RU-6
Rated passenger	额定载客	6
Rated Load Capacity	额定载重量	1000 kg
Pulling Force	牵引力	28KN
Climbing Capacity	爬坡能力	14°
Net weight	净车重量	4000±500 kg
<b>Engine</b>		发动机
Internal combustion engine	内燃机	chinese
Rated power	额定功率	65kW/2400r/min
Emission standard	排放标准	Tier III, Stagelll
Hydraulic torque convertor/Gearbox		液压变矩器/变速箱
DANA 12060A		
Drive axle		桥
DANA		211/111
Wheel base	轴距	2800±50mm
Wheelspan	轮距	1680±50mm
Tyre		轮胎
Specification		规格
8.25R16		
<b>Brake hydraulic system</b>		制动液压系统
Type		类型
posi-stop		
Brake pressure	制动压力	Hydraulic accumulator 8.27MPa, Brake 4MPa
Brake valve	制动阀	MICO/other
<b>Rack</b>		机架
High-tensile structural steel		
<b>Rack</b>		机架
High-tensile structural steel		
Diesel fuel tank	柴油机燃油箱	105 L
Hydraulic oil tank	液压油箱	65 L
<b>Cab</b>		驾驶室
Type		ROPS/FOPS
<b>Size</b>		尺寸
Length	长	4750±100 mm
Width	宽	2040±100 mm
Heigh	高	2230±50 mm
Ground Clearance	离地间隙	240mm
<b>Speed</b> 移动速度		
1	1档	0-6.0 km/h
2	2档	0-13.0 km/h
3	3档	0-23.0 km/h
<b>Steering Radius</b>		转弯半径
Inside Steering Radius	内转弯半径	≤5250 mm
Outside Steering Radius	外转弯半径	≤8100 mm